



## SOLAR SIDING


Wood Facing With Aluminum Honeycomb

High Efficiency Mono Module

250W

1000V

### ENGINEERING DRAWING (mm)



### ELECTRICAL DATA | STC\*

SPECIFICATIONS	SOLAR SIDING WOOD
Nominal Max. Power (Pmax)	250W
MPP Operating Voltage (Vmp)	43.0V
MPP Operating Current (Imp)	5.81A
Open Circuit Voltage (Voc)	48.2V
Short Circuit Current (Isc)	6.79A
Cell Efficiency	22% - 22.5%
Operating Temperature	-40°C ~ +85°C
Max. System Voltage	1000V (IEC/UL)
Max. Series Fuse Rating	20A
Application Classification	Class A

\* Under Standard Test Conditions (STC) of irradiance of 1000 W/m<sup>2</sup>, spectrum AM 1.5 and cell temperature of 25°C.

### MECHANICAL DATA

SPECIFICATIONS	SOLAR SIDING WOOD
Cell Type	Mono-crystalline
Cell Arrangement	72 (12x6)
Dimensions	2030x990mm
Front Cover	3.2 mm tempered glass
Weight	29kg
Back Support	Aluminum Honeycomb
J-Box	IP68, 3 bypass diodes
Cable	4mm <sup>2</sup> , 12 AWG (UL)
Cable Length (including Connector)	1000mm, 1200mm
Connector	MC4

### TEMPERATURE CHARACTERISTICS

SPECIFICATIONS	SOLAR SIDING WOOD
Temperature Coefficient Pmax	-0.36% / °C
Temperature Coefficient Voc	-0.30% / °C
Temperature Coefficient Isc	0.046% / °C
Nominal Module Operating Temperature	42 ± 3°C

Learn More:

 [mitrex.com](http://mitrex.com)

 [info@mitrex.com](mailto:info@mitrex.com)


Headquarters:

 41 Racine Rd., Toronto, ON M9W 2Z4, Canada

 +1 (416) 497 7120

West USA Location:

 10880 Wilshire Blvd Suite 1101, Los Angeles, CA 90024, USA

 +1 (323) 301 7978

East USA Location:

 1 Rockefeller Plaza Fl 11, New York, NY 10020, USA

 +1 (646) 583 4486