

SOLAR PANEL WHITE HP


M395-BIF

High Efficiency Mono Module

395W

1000V

ENGINEERING DRAWING (mm)




ELECTRICAL DATA | STC*

MITREX	WHITE HP M395-BIF
Nominal Max. Power (Pmax)	395W
MPP Operating Voltage (Vmp)	42.1V
MPP Operating Current (Imp)	9.38A
Open Circuit Voltage (Voc)	48.3V
Short Circuit Current (Isc)	9.81A
Module Efficiency	19.5%
Operating Temperature	-40°C ~ +85°C
Max. System Voltage	1000V (IEC/UL)
Max. Series Fuse Rating	20A
Application Classification	Class A

* Under Standard Test Conditions (STC) of irradiance of 1000 W/m², spectrum AM 1.5 and cell temperature of 25°C.

LINEAR PERFORMANCE WARRANTY





- 25 Year Product Warranty
- 25 Year Linear Power Warranty

MECHANICAL DATA

SPECIFICATIONS	WHITE HP M395-BIF
Cell Type	Mono-crystalline
Cell Arrangement	72 [12x6]
Dimensions	2036x996x40mm
Front Cover	3.2 mm tempered glass
Frame	Anodized aluminum alloy silver frame
Weight	22kg
J-Box	IP68, 3 bypass diodes
Cable	4mm ² , 12 AWG (UL)
Cable Length (Including Connector)	300mm, 1000mm, 1200mm
Connector	Staubli MC4

TEMPERATURE CHARACTERISTICS

SPECIFICATIONS	WHITE HP M395-BIF
Temperature Coefficient Pmax	-0.36% / °C
Temperature Coefficient Voc	-0.27% / °C
Temperature Coefficient Isc	0.036% / °C
Nominal Module Operating Temperature	42 ± 3°C



- Datasheet is subjected to change without prior notice, always obtain the most recent version of the datasheet.

- Caution: For professional use only, the installation, handling, and cleaning of PV modules should only be performed by qualified professionals.

Learn More:

- mitrex.com
- info@mitrex.com

Headquarters:

- 41 Racine Rd., Toronto, ON M9W 2Z4, Canada
- +1 (416) 497 7120 (Office Number)
- +1 (855) 254 0214 (Toll Free)

West USA Location:

- 10880 Wilshire Blvd Suite 1101, Los Angeles, CA 90024, USA
- +1 (323) 301 7978

East USA Location:

- 1 Rockefeller Plaza Fl 11, New York, NY 10020, USA
- +1 (646) 583 4486